

Part No. 2510xy240

Ver. 1902

Product Specification

FEATURES:

Premium Line's 24ports wall mount fiber optic box is designed for direct termination of fibers. The box includes two separate sections: one for the fusion splice trays and one for the cable routing. The cable entries/exits are sealed with a flexible grommet, which can be adjusted to the desired cable diameter at installation to protect the inside of the box against dust and debris during and after installation.

- Suitable for SC, ST, FC simplex and LC duplex adapters
- Easy to install and maintain
- Color: grey
- Position of splice cassette adjustable
- Lockable front door
- Dimension 300*350*105 mm
- RoHS compliant



CHARACTERISTICS:

- Perfect and reliable sealing operations
- Splicing, slack storage and distribution
- Easy to operation
- Grounding reliable, protect safe
- Guarantee the curvature radiu
- Apply to extensive field
- Simple installation and maintenance

APPLICATIONS:

• In fiber access, it is designated for fiber termination, protection and distribution.

Premium Line Systems GmbH reserves the right to change specifications without prior notice.



Part No. 2510xy240

Ver. 1902

Product Specification

ORDERING INFORMATION:

Part NO. 2510xy240

Description wall mount fiber optic box, 24ports, without adapters

x: adapter panel 1: simplex 2: duplex(LC only)

Y: type 1: SC 2: ST 3: FC 4: LC

Packing 1pc/box, 5pcs/carton

carton dimension: 62*32.5*37.5 cm, Weight: G.W. 16.80 kg N.W. 17.75 kg

Part No.	Description
251011240	Wall mounted fiber optic box 24 cores SC type, without adapter
251012240	Wall mounted fiber optic box 24 cores ST type, without adapter
251013240	Wall mounted fiber optic box 24 cores FC type, without adapter
251024240	Wall mounted fiber optic box 24×2 cores LC type, without adapter

Premium-Line Systems GmbH, Rosenheimer Str.89, D-83064 Raubling, Germany

► TEL: +49(0)8035 9836 0 ► Fax: +49(0)8035 9836 22

Premium Line Systems GmbH reserves the right to change specifications without prior notice.